



## FLATTING PASTES: EZ FLAT W-30 AQUEOUS SYSTEMS

**EZ FLAT W-30** is an easy to use stir-in dispersion which provides consistent gloss reduction in aqueous systems.

### Applications:

- It is used for making final gloss adjustments which ensures the finished product is within specification and on standard.
- **EZ FLAT AQ** reduces unwanted dust associated with processing dry silica during the manufacturing or compounding process.
- **EZ FLAT AQ** contains amorphous silica for flattening and a polyolefin blend for scratch, scuff and polish resistance.
- The polyolefin blend also provides additional anti-blocking properties when used in topcoats.

**Suggested Incorporating Techniques:** The **EZ FLAT W-30** should always be mixed prior to use. In most cases, the **EZ FLAT W-30** will be more viscous than the systems in which it will be used. Because of this, we recommend pre-mixing it by diluting it with 5 to 10% water and added slowly into the batch while it is under agitation.

**Typical Usage Levels:** Typical use levels range from 5.0 to 15.0%. Use levels are dependent upon the type of resin into which the **EZ FLAT W-30** is being incorporated. Other factors include film thickness and dry time.

### Typical Properties:

Percentage Silica and Polyolefin	31%
Percentage Vehicle (Surfactant)	1%
Percentage Propylene Glycol/Percentage Water	11%/57%
Weight per Gallon (lbs)	9.61
Specific Gravity	1.15
VOC per Gallon (lbs)	3.19

Eagle Specialty Products · 2216 North Broadway · St. Louis, MO 63102  
(314) 241-7771 · (888) 241-9802 · Fax: (314) 241-5356  
[www.espinc.us](http://www.espinc.us)

Our data is based on laboratory tests which are believed to be accurate. However, all recommendations are made without warranty since the conditions of use are beyond the control of Eagle Specialty Products. We do not assume any liability of the product relative to performance or injury resulting from its use. Liability, if any, is limited to replacement product.