



DEFOAMERS: FB 500

AQUEOUS SYSTEMS

FB 500 is a silicone-free defoamer designed specifically for chronic foam problems in dip and flow coatings applications.

Benefits: It is effective in both high and low viscosity coatings. **FB 500** is not only effective at destabilizing surface foam, it also eliminates micro foam within the coating. **FB 500** will not affect intercoat adhesion and may be added at any stage of production, provided it is added while under agitation.

Applications: **FB 500** is effective in water-reducible, alkyd and polyester systems.

Recommended Usage Levels: Use 0.5 to 1.0% based on total formula weight.

Typical Properties:

Appearance	Translucent Liquid
Viscosity (#2 Zahn)	20 ± 5 seconds
Weight per Gallon (lbs)	6.75 ± 0.2
Specific Gravity	0.8103 ± 0.025
pH (10% Dispersion in Water)	7.0-10.0
NV by Weight	100.0 ± 0.5%
NV by Volume	100.0 ± 0.5%
Shelf Life	1 Year
Storage Precaution	Store at room temperature above 40°F
Packaging	390 lbs Drum

Eagle Specialty Products · 2216 North Broadway · St. Louis, MO 63102
(314) 241-7771 · (888) 241-9802 · Fax: (314) 241-5356
www.espinc.us

Our data is based on laboratory tests which are believed to be accurate. However, all recommendations are made without warranty since the conditions of use are beyond the control of Eagle Specialty Products. We do not assume any liability of the product relative to performance or injury resulting from its use. Liability, if any, is limited to replacement product.