



**SUPER DRY 1000** is specially formulated to replace cobalt drier in systems where cobalt can cause adverse side effects.

### Benefits:

- Reduces discoloration of polyurethane during storage
- Improves alkali resistance of polyurethane films
- Prevents loss of dry
- Greatly reduces yellowing of air dry alkyd finishes

**Applications:** Highly effective in oil or alkyd modified polyurethanes as well as in conventional alkyds.

**Recommended Usage Levels:** The following starting point recommendation is based upon 100 lbs of vehicle solids:

- **SUPER DRY 1000**            0.5 Lbs.-0.7 Lbs.
- Zirconium (as metal)       0.1 Lbs.-0.3 Lbs.
- Calcium (as metal)        0.05 Lbs.-0.10 Lbs.

**Optimum Results:** Combine Super Dry 1000 with zirconium and calcium

### Typical Properties:

Weight per Gallon (lbs)	7.1
Specific Gravity	0.85
Solvent	Blend of Xylene and n-Butanol

Eagle Specialty Products · 2216 North Broadway · St. Louis, MO 63102  
(314) 241-7771 · (888) 241-9802 · Fax: (314) 241-5356  
[www.espinc.us](http://www.espinc.us)

Our data is based on laboratory tests which are believed to be accurate. However, all recommendations are made without warranty since the conditions of use are beyond the control of Eagle Specialty Products. We do not assume any liability of the product relative to performance or injury resulting from its use. Liability, if any, is limited to replacement product.