



## WAXES: SUPERSLIP EX

### AQUEOUS SYSTEMS

**SUPERSLIP EX** is a polyethylene with excellent block and abrasion resistance.

**Note:** The components of this product meet the following FDA Status 21CFR:

- Approved under 175.105
- Approved under 175.320 and 176.180 (must meet extractive limits in 176.170(c))
- Approved under 175.3 (extractives not to exceed 0.5 mg per square inch per extractive limits in 175.300)
- Approved under 176.170 for food Type VII-B only if no extractive limitations performed
- Approved for other food types and conditions of use (must meet extractive limitations in 176.170(c))

#### Typical Properties:

Wax	Polyethylene
Percentage Solids	25%
Volatiles	Water
Average Particle Size	45nm
Specific Gravity	1.01
Viscosity (CPS)	<20 #1 Spindle @60RPM

Eagle Specialty Products · 2216 North Broadway · St. Louis, MO 63102  
(314) 241-7771 · (888) 241-9802 · Fax: (314) 241-5356  
[www.espinc.us](http://www.espinc.us)

Our data is based on laboratory tests which are believed to be accurate. However, all recommendations are made without warranty since the conditions of use are beyond the control of Eagle Specialty Products. We do not assume any liability of the product relative to performance or injury resulting from its use. Liability, if any, is limited to replacement product.